











STAINLESS STEEL HOUSING AND TUNGSTEN CARBIDE WEAR SURFACES TO EXTEND LIFE







Greater impingement allows you to use smaller nozzle sizes while getting the same impact as nozzles with higher GPM.

NOZZLE SIZE	NOZZLE PART NUMBER	FLOW RATE CHART (GPM)					
		70 Bar (@ 1000 PSI)	103 Bar (@ 1500 PSI)	138 Bar (@ 2000 PSI)	172 Bar (@ 2500 PSI)	207 Bar (@ 3000 PSI)	221 Bar (@ 3200 PSI)
6.0	20022427	11.4 LPM (3.0 GPM)	14.0 LPM (3.7 GPM)	15.9 LPM (4.2 GPM)	17.8 LPM (4.7 GPM)	19.7 LPM (5.2 GPM)	20.4 LPM (5.4 GPM)
8.0	20022428	15.1 LPM (4.0 GPM)	18.5 LPM (4.9 GPM)	21.6 LPM (5.7 GPM)	23.8 LPM (6.3 GPM)	26.1 LPM (6.9 GPM)	27.3 LPM (7.2 GPM)
10.0	20022429	18.9 LPM (5.0 GPM)	23.1 LPM (6.1 GPM)	26.9 LPM (7.1 GPM)	29.9 LPM (7.9 GPM)	32.9 LPM (8.7 GPM)	33.7 LPM (8.9 GPM)
REBUILD KITS AND REPLACEMENT COVERS AVAILABLE – CONTACT YOUR LOCAL DEALER TO PURCHASE							